

DOMOFIX-LM

Solvent-containing Adhesive for vapour barriers based on synthetic rubber

Properties: • high steam tightness

high elasticity

resistant to froststrong adhesion

permanent self-adhesive

adheres to almost all substrates

permanent moisture-resistant compoundadheres to wet and slightly oily substrates

Range of application:

The adhesive is suitable for the gluing of vapour barriers and vapour locks well as foils on brickwork and tilework, concrete, wood, plaster, metal.

· remains permanently elastic

not suitable for polystyrene

Instructions for use:

Surfaces have to be clean, dry, solid and free of grease. Apply a bead of at least 8 mm to the surface. Press the foil onto the bead. Can be used with or without pressure slat. Do not put weight on the building part during the drying process 1-2 days).

Packaging: 300 ml cartridge

600 ml plastic bags

Storage: Shelf life: 2 years at room temperature

Storage temperature: not over 60 °C, resistant to frost

Technical data: Chemical basis: rubber / soluble resin

Colour: white, other colours on request

Density: 0.95 g/cm³

Drying time: max. 5 - 8 minutes Working temperature: $+ 5 ^{\circ}\text{C} - + 50 ^{\circ}\text{C}$ Temperature resistance: $- 25 ^{\circ}\text{C} - + 100 ^{\circ}\text{C}$

Capacity: 8 mm x 8 mm: 5 metres per cartridge

Safety note: Flammable. Repeated contact can lead to dry or rough skin. Vapours can cause sleepiness drowsiness. Do not inhale vapour. Avoid contact with eyes or skin. Dispose of empty containers safely.

BADEN-CHEMIE GmbH D-76534 Baden-Baden

(+49 (0) 7223 / 96680 Fax: +49 (0) 7223 / 966850 e-mail: info@baden-chemie.de www.baden-chemie.

The publication of this technical data sheet invalidates all previous editions. We guarantee the quality of our materia accordance with our terms and conditions of sale and delivery. On account of the many different substrates and method application, we cannot accept liability for the success of the application. Therefore we recommend that preliminary to for suitability be undertaken by the customer.

10/04