

# DOMOFIX-PU

**Highest adhesive strength ■ Solvent-free**  
**Polyurethane-adhesive for vapour barriers**

**Properties:**

- solvent-free
- neutral in smell
- strong adhesion
- permanent airtight
- for gluing of foils, stuffings, cardboards
- permanent self-adhesive and elastic

**Range of application:**

- The adhesive is suitable for the gluing of vapour barriers and vapour locks ; well as foils on brickwork and tilework , concrete, wood, plaster, metal.

**Instructions for use:**

Surfaces have to be clean, dry, solid and free of grease. Apply a bead of at least 8 mm to the surface. For maximum adhesion let the adhesive dry for 30 minutes. Then, press the building part lightly onto the bead. Can be used with and without a pressure slat. Do not put weight on the building part during the drying process (2-3 days). The freshly applied DOMOFIX-PU has to be protected from moisture.

**Packaging:**

300 ml cartridge  
400 ml plastic bags  
600 ml plastic bags

**Storage:**

Shelf life: 1 year at room temperature  
Storage temperature: not over 60 °C, not resistant to frost

**Technical data:**

Chemical basis: watery dispersion on the basis of polyurethane  
Colour: light blue  
Density: 1.17 g/ml (20 °C)  
Drying time: at least 30 minutes  
Working temperature: + 5 °C - + 50 °C  
Temperature resistance: - 25 °C - + 80 °C  
Capacity: 8 mm x 8 mm: 5 metres per cartridge

**Safety note:** Keep out of reach of children

**BADEN-CHEMIE GmbH D-76534 Baden-Baden**

( +49 (0) 7223 / 96680

Fax: +49 (0) 7223 / 966850

e-mail: [info@baden-chemie.de](mailto:info@baden-chemie.de)

[www.baden-chemie.de](http://www.baden-chemie.de)

The publication of this technical data sheet invalidates all previous editions. We guarantee the quality of our material in accordance with our terms and conditions of sale and delivery. On account of the many different substrates and methods of application, we cannot accept liability for the success of the application. Therefore we recommend that preliminary tests for suitability be undertaken by the customer.

10/04